

Cisco Aironet 1850 Series Access Points

Contents

Product overview	3
Features and benefits	3
Product specifications	4
Warranty information	13
Ordering information	13
Cisco Services	14
Cisco Capital	14



Product overview

Ideal for small and medium-sized networks, the Cisco® Aironet® 1850 Series delivers industry-leading performance for enterprise and service provider markets via enterprise-class 4x4 MIMO, four-spatial-stream access points that support the IEEE's new 802.11ac Wave 2 specification. The Aironet 1850 Series extends support to a new generation of Wi-Fi clients, such as smartphones, tablets, and high-performance laptops that have integrated 802.11ac Wave 1 or Wave 2 support.

Features and benefits

With 802.11ac Wave 2, the Aironet 1850 Series provides a data rate of up to 1.7 Gbps on the 5-GHz radio, more than triple the rates offered by today's high-end 802.11n access points. It also enables a total aggregate dual-radio data rate of 2.0 Gbps, providing the necessary foundation for enterprise and service provider networks to stay ahead of the performance and bandwidth expectations and needs of their wireless users.

Due to its convenience, wireless access is increasingly the preferred form of network connectivity for corporate users. Along with this shift, there is an expectation that wireless should not slow down users' day-to-day work, but should enable a high-performance experience while allowing users to move freely. The 1850 Series delivers industry-leading performance for highly secure and reliable wireless connections and provides a robust mobility experience that includes:

- 802.11ac Wave 2 with 4x4 Multiple-Input Multiple-Output (MIMO) technology with four spatial streams when operating in single-user MIMO mode and three spatial streams while operating in multiuser MIMO mode, offering 1.7-Gbps rates for more capacity and reliability than competing access points.
- Multiuser MIMO, allowing transmission of data to multiple 802.11ac Wave 2 capable clients simultaneously to improve client experience. Prior to multiuser MIMO, 802.11n and 802.11ac Wave 1 access points could transmit data to only one client at a time, typically referred to as single-user MIMO.
- Transmit beamforming technology to improve downlink performance to mobile devices, including one-, two-, and three-spatial-stream devices on 802.11ac, while improving battery life on mobile devices such as smartphones and tablets.
- Flexible deployment mode through the Cisco Mobility Express Solution is ideal for small to medium-sized deployments that require multiple access points. Easy setup allows the 1850 Series to be deployed on networks without a physical controller.

All of these features help ensure the best possible end-user experience on the wireless network. Cisco also offers the industry's broadest selection of [802.11n and 802.11ac antennas](#), delivering optimal coverage for a variety of deployment scenarios.

The Cisco Aironet 1850 Series Access Points also support:

- The Onyx **BLE Beacon Solution**, which provides a feature that the Aironet access points are missing: built-in Bluetooth Low Energy (BLE). The Onyx BLE Beacons work smoothly with indoor location-based services. Used for indoor navigation, proximity marketing, and asset tracking, BLE is a tool that is becoming more and more useful with each passing day. With the Onyx BLE Beacons, customers can add BLE to their networks.

Product specifications

Table 1. Product specifications

Feature	Specifications
Software	Cisco Unified Wireless Network Software Release with AireOS wireless controllers: <ul style="list-style-type: none"> • 8.1 MR1 or later for the Cisco Aironet 1850 Series Access Points
Deployment modes	Centralized local, Standalone [*] , Sniffer, Cisco FlexConnect [™] , Monitor ^{**} , OfficeExtend ^{**} , Mesh ^{**}
Supported wireless LAN controllers	<ul style="list-style-type: none"> • Cisco 2500 Series Wireless Controllers, Cisco 3500 series Wireless Controllers, Cisco Wireless Controller Module for ISR G2, Cisco Wireless Services Module 2 (WiSM2) for Catalyst[®] 6500 Series Switches, Cisco 5500 Series Wireless Controllers, Cisco Flex[®] 7500 Series Wireless Controllers, Cisco 8500 Series Wireless Controllers, Cisco 9800 series Wireless Controllers, Cisco 5760 Series Wireless Controllers ^{**}, Cisco Catalyst 3650/3850 Series switch with integrated controller ^{**} • Cisco Mobility Express
802.11n version 2.0 (and related) capabilities	<ul style="list-style-type: none"> • 4x4 MIMO with four spatial streams • Maximal Ratio Combining (MRC) • 20- and 40-MHz channels • PHY data rates up to 600 Mbps (40 MHz with 5 GHz) • Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) • 802.11 Dynamic Frequency Selection (DFS) • Cyclic Shift Diversity (CSD) support
802.11ac Wave 1 and 2 capabilities	<ul style="list-style-type: none"> • 4x4 MIMO with four spatial streams, single-user MIMO • 4x4 MIMO with three spatial streams, multiuser MIMO • MRC • 802.11ac beamforming (transmit beamforming) • 20-, 40-, and 80-MHz channels • PHY data rates up to 1.7 Gbps (80 MHz in 5 GHz) • Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) • 802.11 DFS • CSD support • Rogue device detection

Feature	Specifications				
Data rates supported	802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps				
	802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps				
	802.11n data rates on 2.4 GHz (only 20 MHz and MCS 0 to MCS 23) and 5 GHz:				
	MCS Index ¹	GI ² = 800 ns	GI = 800 ns	GI = 400 ns	GI = 400 ns
		20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	20-MHz Rate (Mbps)	40-MHz Rate (Mbps)
	0	6.5	13.5	7.2	15
	1	13	27	14.4	30
	2	19.5	40.5	21.7	45
	3	26	54	28.9	60
	4	39	81	43.3	90
5	52	108	57.8	120	
6	58.5	121.5	65	135	

¹ MCS Index: The Modulation and Coding Scheme (MCS) index determines the number of spatial streams, the modulation, the coding rate, and data rate values.

² GI: A Guard Interval (GI) between symbols helps receivers overcome the effects of multipath delay spreads.

Feature	Specifications				
Data rates supported	MCS Index ³	GI ⁴ = 800 ns	GI = 800 ns	GI = 400 ns	GI = 400 ns
		20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	20-MHz Rate (Mbps)	40-MHz Rate (Mbps)
	7	65	135	72.2	150
	8	13	27	14.4	30
	9	26	54	28.9	60
	10	39	81	43.3	90
	11	52	108	57.8	120
	12	78	162	86.7	180
	13	104	216	115.6	240
	14	117	243	130	270
	15	130	270	144.4	300
	16	19.5	40.5	21.7	45
	17	39	81	43.3	90
	18	58.5	121.5	65	135
19	78	162	86.7	180	
20	117	243	130	270	
21	156	324	173.3	360	

Feature	Specifications						
	22	175.5	364.5	195	405		
	23	195	405	216.7	450		
	24	26	54	28.9	60		
	25	52	108	57.8	120		
	26	78	162	86.7	180		
	27	104	216	115.6	240		
	28	156	324	173.3	360		
	29	208	432	231.1	480		
	30	234	486	260	540		
	31	260	540	288.9	600		
802.11ac data rates (5 GHz):							
MCS Index	Spatial Streams	GI = 800 ns			GI = 400 ns		
		20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	80-MHz Rate (Mbps)	20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	80-MHz Rate (Mbps)
0	1	6.5	13.5	29.3	7.2	15	32.5
1	1	13	27	58.5	14.4	30	65
2	1	19.5	40.5	87.8	21.7	45	97.5
3	1	26	54	117	28.9	60	130
4	1	39	81	175.5	43.3	90	195
5	1	52	108	234	57.8	120	260
6	1	58.5	121.5	263.3	65	135	292.5
7	1	65	135	292.5	72.2	150	325
8	1	78	162	351	86.7	180	390

³ MCS Index: The Modulation and Coding Scheme (MCS) index determines the number of spatial streams, the modulation, the coding rate, and data rate values.

⁴ GI: A Guard Interval (GI) between symbols helps receivers overcome the effects of multipath delay spreads.

Feature	Specifications							
	MCS index	Spatial streams	GI = 800 ns			GI = 400 ns		
			20-MHz rate (Mbps)	40-MHz rate (Mbps)	80-MHz rate (Mbps)	20-MHz rate (Mbps)	40-MHz rate (Mbps)	80-MHz rate (Mbps)
9	1	-	180	390	-	200	433.3	
0	2	13	27	58.5	14.4	30	65	
1	2	26	54	117	28.9	60	130	
2	2	39	81	175.5	43.3	90	195	
3	2	52	108	234	57.8	120	260	
4	2	78	162	351	86.7	180	390	
5	2	104	216	468	115.6	240	520	
6	2	117	243	526.5	130	270	585	
7	2	130	270	585	144.4	300	650	
8	2	156	324	702	173.3	360	780	
9	2	-	360	780	-	400	866.7	
0	3	19.5	40.5	87.8	21.7	45	97.5	
1	3	39	81	175.5	43.3	90	195	
2	3	58.5	121.5	263.3	65	135	292.5	
3	3	78	162	351	86.7	180	390	
4	3	117	243	526.5	130	270	585	
5	3	156	324	702	173.3	360	780	
6	3	175.5	364.5	-	195	405	-	
7	3	195	405	877.5	216.7	450	975	
8	3	234	486	1053	260	540	1170	
9	3	260	540	1170	288.9	600	1300	
0	4	26	54	117	28.9	60	130	
1	4	52	108	234	57.8	120	260	
2	4	78	162	351	86.7	180	390	
3	4	104	216	468	115.6	240	520	
4	4	156	324	702	173.3	360	780	
5	4	208	432	936	231.1	480	1040	
6	4	234	486	1053	260	540	1170	
7	4	260	540	1170	288.9	600	1300	
8	4	312	648	1404	346.7	720	1560	
9	4	-	720	1560	-	800	1733.3	

Feature	Specifications	
Maximum number of nonoverlapping channels	<p>A (A regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.462 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.500 to 5.700 GHz; 8 channels (excludes 5.600 to 5.640 GHz) • 5.745 to 5.825 GHz; 5 channels <p>B (B regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.462 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.500 to 5.720 GHz; 12 channels • 5.745 to 5.825 GHz; 5 channels <p>C (C regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.745 to 5.825 GHz; 5 channels <p>D (D regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.462 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.745 to 5.825 GHz; 5 channels <p>E (E regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.500 to 5.700 GHz; 8 channels (excludes 5.600 to 5.640 GHz) <p>F (F regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.745 to 5.825 GHz; 4 channels <p>H (H regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.150 to 5.350 GHz; 8 channels • 5.745 to 5.825 GHz; 5 channels <p>I (I regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels 	<p>K (K regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.500 to 5.620 GHz; 7 channels • 5.745 to 5.805 GHz; 4 channels <p>N (N regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.462 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.745 to 5.825 GHz; 5 channels <p>Q (Q regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.500 to 5.700 GHz; 11 channels <p>R (R regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.660 to 5.805 GHz; 7 channels <p>S (S regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.472 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.500 to 5.700 GHz; 11 channels • 5.745 to 5.825 GHz; 5 channels <p>T (T regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.462 GHz; 3 channels • 5.280 to 5.320 GHz; 3 channels • 5.500 to 5.700 GHz; 8 channels (excludes 5.600 to 5.640 GHz) • 5.745 to 5.825 GHz; 5 channels <p>Z (Z regulatory domain):</p> <ul style="list-style-type: none"> • 2.412 to 2.462 GHz; 3 channels • 5.180 to 5.320 GHz; 8 channels • 5.500 to 5.700 GHz; 8 channels (excludes 5.600 to 5.640 GHz) • 5.745 to 5.825 GHz; 5 channels

Note: Customers are responsible for verifying approval for use in their individual countries. To verify approval that corresponds to a particular country, visit <https://www.cisco.com/go/aironet/compliance>.

Feature	Specifications
Maximum number of nonoverlapping channels	<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <p>2.4 GHz</p> <ul style="list-style-type: none"> • 802.11b/g: <ul style="list-style-type: none"> ◦ 20 MHz: 3 • 802.11n: <ul style="list-style-type: none"> ◦ 20 MHz: 3 </div> <div style="width: 48%;"> <p>5 GHz</p> <ul style="list-style-type: none"> • 802.11a: <ul style="list-style-type: none"> ◦ 20 MHz: 25 • 802.11n: <ul style="list-style-type: none"> ◦ 20 MHz: 25 ◦ 40 MHz: 12 • 802.11ac: <ul style="list-style-type: none"> ◦ 20 MHz: 21 ◦ 40 MHz: 12 ◦ 80 MHz: 6 </div> </div>

Note: This varies by regulatory domain. Refer to the product documentation for specific details for each regulatory domain.

Receive sensitivity	<ul style="list-style-type: none"> • 802.11b (CCK) <ul style="list-style-type: none"> ◦ -101 dBm @ 1 Mbps ◦ -98 dBm @ 2 Mbps ◦ -92 dBm @ 5.5 Mbps ◦ -89 dBm @ 11 Mbps 	<ul style="list-style-type: none"> • 802.11g (non HT20) <ul style="list-style-type: none"> ◦ -96 dBm @ 6 Mbps ◦ -95 dBm @ 9 Mbps ◦ -94 dBm @ 12 Mbps ◦ -92 dBm @ 18 Mbps ◦ -88 dBm @ 24 Mbps ◦ -85 dBm @ 36 Mbps ◦ -81 dBm @ 48 Mbps ◦ -79 dBm @ 54 Mbps 	<ul style="list-style-type: none"> • 802.11a (non HT20) <ul style="list-style-type: none"> ◦ -96 dBm @ 6 Mbps ◦ -95 dBm @ 9 Mbps ◦ -94 dBm @ 12 Mbps ◦ -92 dBm @ 18 Mbps ◦ -88 dBm @ 24 Mbps ◦ -85 dBm @ 36 Mbps ◦ -80 dBm @ 48 Mbps ◦ -79 dBm @ 54 Mbps 	
	<p>2.4 GHz</p> <ul style="list-style-type: none"> • 802.11n (HT20) <ul style="list-style-type: none"> ◦ -96 dBm @ MCS0 ◦ -93 dBm @ MCS1 ◦ -90 dBm @ MCS2 ◦ -87 dBm @ MCS3 ◦ -84 dBm @ MCS4 ◦ -79 dBm @ MCS5 ◦ -78 dBm @ MCS6 ◦ -76 dBm @ MCS7 ◦ -93 dBm @ MCS8 ◦ -90 dBm @ MCS9 ◦ -87 dBm @ MCS10 ◦ -84 dBm @ MCS11 ◦ -81 dBm @ MCS12 ◦ -76 dBm @ MCS13 ◦ -75 dBm @ MCS14 ◦ -73 dBm @ MCS15 ◦ -91 dBm @ MCS16 ◦ -88 dBm @ MCS17 ◦ -85 dBm @ MCS18 ◦ -82 dBm @ MCS19 ◦ -79 dBm @ MCS20 ◦ -74 dBm @ MCS21 ◦ -73 dBm @ MCS22 ◦ -71 dBm @ MCS23 		<p>5 GHz</p> <ul style="list-style-type: none"> • 802.11n (HT20) <ul style="list-style-type: none"> ◦ -96 dBm @ MCS0 ◦ -92 dBm @ MCS1 ◦ -90 dBm @ MCS2 ◦ -86 dBm @ MCS3 ◦ -83 dBm @ MCS4 ◦ -79 dBm @ MCS5 ◦ -77 dBm @ MCS6 ◦ -76 dBm @ MCS7 ◦ -93 dBm @ MCS8 ◦ -89 dBm @ MCS9 ◦ -87 dBm @ MCS10 ◦ -83 dBm @ MCS11 ◦ -80 dBm @ MCS12 ◦ -76 dBm @ MCS13 ◦ -74 dBm @ MCS14 ◦ -73 dBm @ MCS15 ◦ -91 dBm @ MCS16 ◦ -87 dBm @ MCS17 ◦ -85 dBm @ MCS18 ◦ -81 dBm @ MCS19 ◦ -78 dBm @ MCS20 ◦ -74 dBm @ MCS21 ◦ -72 dBm @ MCS22 ◦ -71 dBm @ MCS23 ◦ -89 dBm @ MCS24 ◦ -85 dBm @ MCS25 ◦ -83 dBm @ MCS26 	<p>5 GHz</p> <ul style="list-style-type: none"> • 802.11n (HT40) <ul style="list-style-type: none"> ◦ -93 dBm @ MCS0 ◦ -90 dBm @ MCS1 ◦ -87 dBm @ MCS2 ◦ -84 dBm @ MCS3 ◦ -80 dBm @ MCS4 ◦ -76 dBm @ MCS5 ◦ -75 dBm @ MCS6 ◦ -73 dBm @ MCS7 ◦ -90 dBm @ MCS8 ◦ -87 dBm @ MCS9 ◦ -84 dBm @ MCS10 ◦ -81 dBm @ MCS11 ◦ -77 dBm @ MCS12 ◦ -73 dBm @ MCS13 ◦ -72 dBm @ MCS14 ◦ -70 dBm @ MCS15 ◦ -88 dBm @ MCS16 ◦ -85 dBm @ MCS17 ◦ -82 dBm @ MCS18 ◦ -79 dBm @ MCS19 ◦ -75 dBm @ MCS20 ◦ -71 dBm @ MCS21 ◦ -70 dBm @ MCS22 ◦ -68 dBm @ MCS23 ◦ -86 dBm @ MCS24 ◦ -83 dBm @ MCS25 ◦ -80 dBm @ MCS26

Feature	Specifications				
			<ul style="list-style-type: none"> ◦ -79 dBm @ MCS27 ◦ -76 dBm @ MCS28 ◦ -72 dBm @ MCS29 ◦ -70 dBm @ MCS30 ◦ -69 dBm @ MCS31 	<ul style="list-style-type: none"> ◦ -77 dBm @ MCS27 ◦ -73 dBm @ MCS28 ◦ -69 dBm @ MCS29 ◦ -68 dBm @ MCS30 ◦ -66 dBm @ MCS31 	
	802.11ac receive sensitivity				
	802.11ac (non HT80)				
	<ul style="list-style-type: none"> • -89 dBm @ 6 Mbps • -73 dBm @ 54 Mbps 				
	MCS index	Spatial streams			
			VHT20	VHT40	VHT80
	0	1	-96 dBm	-93 dBm	-89 dBm
	7	1	-76 dBm	-73 dBm	-70 dBm
	8	1	-71 dBm	-69 dBm	-66 dBm
	9	1	NA	-67 dBm	-64 dBm
	0	2	-93 dBm	-90 dBm	-86 dBm
	7	2	-73 dBm	-70 dBm	-67 dBm
	8	2	-68 dBm	-66 dBm	-63 dBm
	9	2	NA	-64 dBm	-61 dBm
	0	3	-91 dBm	-88 dBm	-84 dBm
	7	3	-71 dBm	-68 dBm	-65 dBm
	8	3	-66 dBm	-64 dBm	-61 dBm
	9	3	-64 dBm	-62 dBm	-59 dBm
	MCS index	Spatial streams			
			VHT20	VHT40	VHT80
	0	4	-89 dBm	-86 dBm	-82 dBm
	7	4	-69 dBm	-66 dBm	-63 dBm
	8	4	-64 dBm	-62 dBm	-59 dBm
	9	4	NA	-60 dBm	-57 dBm
Maximum transmit power	2.4 GHz		5 GHz		
	<ul style="list-style-type: none"> • 802.11b <ul style="list-style-type: none"> ◦ 22 dBm, 3 antennas • 802.11g <ul style="list-style-type: none"> ◦ 22 dBm, 3 antennas • 802.11n (HT20) <ul style="list-style-type: none"> ◦ 22 dBm, 3 antennas 		<ul style="list-style-type: none"> • 802.11a <ul style="list-style-type: none"> ◦ 23 dBm, 4 antennas • 802.11n (HT20) <ul style="list-style-type: none"> ◦ 23 dBm, 4 antennas • 802.11n (HT40) <ul style="list-style-type: none"> ◦ 23 dBm, 4 antennas 		

Feature	Specifications	
	<ul style="list-style-type: none"> • 802.11ac <ul style="list-style-type: none"> ◦ non-HT80: 23 dBm, 4 antennas ◦ VHT20: 23 dBm, 4 antennas ◦ VHT40: 23 dBm, 4 antennas ◦ VHT80: 23 dBm, 4 antennas 	
<p>Note: The maximum power setting will vary by channel and according to individual country regulations. Refer to the product documentation for specific details.</p>		
Available transmit power settings	2.4 GHz <ul style="list-style-type: none"> • 22 dBm • 19 dBm • 16 dBm • 13 dBm • 10 dBm • 7 dBm • 4 dBm • 1 dBm 	5 GHz <ul style="list-style-type: none"> • 23 dBm • 20 dBm • 17 dBm • 14 dBm • 11 dBm • 8 dBm • 5 dBm • 2 dBm
<p>Note: The maximum power setting will vary by channel and according to individual country regulations. Refer to the product documentation for specific details.</p>		
Integrated antenna	<ul style="list-style-type: none"> • 2.4 GHz, gain 3 dBi, internal omni, horizontal beamwidth 360° • 5 GHz, gain 5 dBi, internal omni, horizontal beamwidth 360° 	
External antenna (sold separately)	<ul style="list-style-type: none"> • Certified for use with antenna gains up to 6 dBi (2.4 GHz and 5 GHz) • Cisco offers the industry's broadest selection of antennas, delivering optimal coverage for a variety of deployment scenarios 	
Interfaces	<ul style="list-style-type: none"> • 1 x 10/100/1000BASE-T autosensing (RJ-45), Power over Ethernet (PoE) • 1 x 10/100/1000BASE-T autosensing (RJ-45), AUX (used for Link Aggregation) • Management console port (RJ-45) • USB 2.0 (enabled via future software) 	
Indicators	<ul style="list-style-type: none"> • Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors 	
Dimensions (W x L x H)	<ul style="list-style-type: none"> • Access point (without mounting bracket): 8.3 x 8.3 x 2 in. (210.8 x 210.8 x 50.8 mm) 	
Weight	<ul style="list-style-type: none"> • 3.12 lb (1.41 kg) 	
Environmental	<p>Cisco Aironet 1850i</p> <ul style="list-style-type: none"> • Nonoperating (storage) temperature: -22° to 158°F (-30° to 70°C) • Nonoperating (storage) altitude test: 25°C, 15,000 ft. • Operating temperature: 32° to 104°F (0° to 40°C) • Operating humidity: 10% to 90% (noncondensing) • Operating altitude test: 40°C, 9843 ft. <p>Cisco Aironet 1850e</p> <ul style="list-style-type: none"> • Nonoperating (storage) temperature: -22° to 158°F (-30° to 70°C) • Nonoperating (storage) altitude test: 25°C, 15,000 ft. 	

Feature	Specifications
	<ul style="list-style-type: none"> Operating temperature: -4° to 122°F (-20° to 50°C) Operating humidity: 10% to 90% (noncondensing) Operating altitude test: 40 °C, 9843 ft.
System memory	<ul style="list-style-type: none"> 1 GB DRAM 256 MB flash
Input power requirements	<ul style="list-style-type: none"> AP1850: 44 to 57 VDC Power supply and power injector: 100 to 240 VAC; 50 to 60 Hz
Power draw	<ul style="list-style-type: none"> 20.9W <p>Note: When deployed using a Power over Ethernet (PoE) specification, the power drawn from the power sourcing equipment will be higher by some amount, depending on the length of the interconnecting cable.</p>
Powering options	<ul style="list-style-type: none"> 802.3at Enhanced PoE Cisco power injector, AIR-PWRINJ4= Cisco local power supply, AIR-PWR-C= Cisco power injector, AIR-PWRINJ5= (Note: this injector supports 802.3af only) 802.3af <p>Note: If 802.3af PoE is the source of power, (1) the 1852e 2.4-GHz radio will shift to 2x3 from 3x4, (2) The USB port and AUX Ethernet port are disabled on both the 1852i and 1852e.</p>
Warranty	Limited lifetime hardware warranty
Compliance standards	<ul style="list-style-type: none"> UL 60950-1 CAN/CSA-C22.2 No. 60950-1 UL 2043 IEC 60950-1 EN 60950-1 EN 50155 for 2800e (Operating temperature -20° to 50°C) Radio approvals: <ul style="list-style-type: none"> FCC Part 15.247, 15.407* RSS-210 (Canada) EN 300.328, EN 301.893 (Europe) ARIB-STD 66 (Japan) ARIB-STD T71 (Japan) EMI and susceptibility (Class B) FCC Part 15.107 and 15.109* ICES-003 (Canada) VCCI (Japan) EN 301.489-1 and -17 (Europe) EN 60601-1-2 EMC requirements for the Medical Directive 93/42/EEC IEEE standards: <ul style="list-style-type: none"> IEEE 802.11a/b/g, 802.11n, 802.11h, 802.11d IEEE 802.11ac Draft 5 Security: <ul style="list-style-type: none"> 802.11i, Wi-Fi Protected Access 2 (WPA2), WPA 802.1X Advanced Encryption Standard (AES) Extensible Authentication Protocol (EAP) types:

Feature	Specifications
	<ul style="list-style-type: none"> ◦ EAP-Transport Layer Security (TLS) ◦ EAP-Tunneled TLS (TTLS) or Microsoft Challenge Handshake Authentication Protocol Version 2 (MSCHAPv2) ◦ Protected EAP (PEAP) v0 or EAP-MSCHAPv2 ◦ EAP-Flexible Authentication via Secure Tunneling (FAST) ◦ PEAP v1 or EAP-Generic Token Card (GTC) ◦ EAP-Subscriber Identity Module (SIM) ● Multimedia: <ul style="list-style-type: none"> ◦ Wi-Fi Multimedia (WMM) ● Other: <ul style="list-style-type: none"> ◦ FCC Bulletin OET-65C ◦ RSS-102

* Supported via Cisco Mobility Express with controller function running on the access point - not Cisco IOS® Software Autonomous based.

** Future.

Warranty information

The Cisco Aironet 1850 Series Access Points come with a limited lifetime warranty that provides full warranty coverage of the hardware for as long as the original end user continues to own or use the product. The warranty includes 10-day advance hardware replacement and ensures that software media are defect-free for 90 days. For more details, visit <https://www.cisco.com/go/warranty>.

Ordering information

To place an order, visit the [Cisco How to Buy page](#). To download software, visit the [Cisco Software Center](#).

Table 2. Ordering information

Product name	Part number
Aironet 1850 Series	Cisco Aironet 1852i Access Point: Indoor environments, with internal antennas <ul style="list-style-type: none"> ● AIR-AP1852I-x-K9: Dual-band, controller-based 802.11a/g/n/ac, Wave 2 ● AIR-AP1852I-x-K9C: Dual-band, controller-based 802.11a/g/n/ac, Wave 2, configurable ● Regulatory domains: (x = regulatory domain)
	Cisco Aironet 1852e Access Point: Indoor, challenging environments, with external antennas <ul style="list-style-type: none"> ● AIR-AP1852E-x-K9: Dual-band, controller-based 802.11a/g/n/ac, Wave 2 ● AIR-AP1852E-x-K9C: Dual-band, controller-based 802.11a/g/n/ac, Wave 2, configurable ● Regulatory domains: (x = regulatory domain) <p>Customers are responsible for verifying approval for use in their individual countries. To verify approval that corresponds to a particular country or the regulatory domain used in a specific country, visit https://www.cisco.com/go/aironet/compliance.</p> <p>Not all regulatory domains have been approved. As they are approved, the part numbers will be available on the Global Price List.</p>

Cisco Services

Realize the full business value of your technology investments faster with intelligent, customized services from Cisco and our partners. Backed by deep networking expertise and a broad ecosystem of partners, Cisco Wireless LAN Services help you deploy a sound, scalable mobility network that enables rich media collaboration while improving the operational efficiency gained from a converged wired and wireless network infrastructure based on the Cisco Unified Wireless Network. Together with partners, we offer expert plan, build, and run services to accelerate your transition to advanced mobility services while continuously optimizing the performance, reliability, and security of that architecture after it is deployed.

Cisco Wireless LAN Services

- AS-WLAN-CNSLT: [Cisco Wireless LAN Network Planning and Design Service](#)
- AS-WLAN-CNSLT: [Cisco Wireless LAN 802.11n Migration Service](#)
- AS-WLAN-CNSLT: [Cisco Wireless LAN Performance and Security Assessment Service](#)

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more](#).

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)