

L18-S\\\300 18" High Power


Extended Low Frequency Speaker

4" INSIDE/OUTSIDE Copper Voice Coil **VENTED ALUMINIUM Die-Cast Frame**


High Power & Superior Performance for

Applications

Dimensions



Frequency Response Curve



■ Features

- Powerful and reliable speaker for various bass & subwoofer applications.
- Robust aluminium die-cast frame with dual forced air ventilation for efficient heat dissipation.
- GLASS FIBRE former voice coil for withstanding high temperatures.
- b 4" INSIDE/OUTSIDE copper voice coil.
- Triple roll surround and re-inforced conex spider for improvec linearity control.
- Ideal professional bass speaker for live music, sound reinforcement and all PA applications.

Specifications

•		
POWER RATING		800W RMS
NOMINAL DIAMETER		457 mm (18")
NOMINAL IMPEDANCE		8Ω
SENSITIVITY (1W/1m)		98dB
MAGNET WEIGHT		4.60kg
RESONANT FREQUENCEY	(Fs)	41Hz
DC RESISTANCE	(Re)	5.4Ω
ELECTROMAGNETIC Q	(Qes)	0.38
MECHANICAL Q	(Qms)	11.10
TOTAL Q	(Qts)	0.37
COMPLIANCE EQUIVALENT VOL	UME (VAS)	176 Litr
SURFACE AREA OF CONE	(Sd)	1225cm ²
REFERENCE EFFICIENCY	(η o)	2.8%
VOICE COIL DIAMETER	·	4.0"
OVERHANG	(Xmax)	8.0 mm
MOVING MASS	(Mms)	185gm
BL PRODUCT	(BL)	25.3TM
COIL INDUCTANCE	(Le)	2.1mH
OVERALL DIAMETER		47 8 mm
DEPTH		189 mm
BAFFLE HOLE DIAMETER		427 mm
BOLT MOUNT DIAMETER	(PCD)	451 mm (8 Bolts)
WEIGHT		12.80kg

Design and Specifications are subject to change without notice owing to continuous product up-gradation. Technical specifications are subject to production tolerances. We cannot be held responsible for printing errors, should they occur. अमध्यक is a registered trademark of Ahuja Radios in India and other countries © Copyright Ahuja Radios, 2018. All rights reserved. Any unauthorized reproduction or use of logos, images or design elements is strictly prohibited by law. No part of this compilation may be reproduced in any manner or translated without written permission.

AHUJA RADIOS

E. & O. E. 2K/05/17