### 5MP IR Dome Camera with 6mm Lens







SATATYA CIDR50FL60CWP 5MP IR Dome Camera with 6mm Lens

Matrix Project Series IP Cameras are built using superior components such as Sony STARVIS sensor and higher MTF lens to offer unmatched image quality especially during the low light conditions. Powered by True WDR algorithm, these cameras offer consistent image quality even in highly varying lighting conditions. Built in intelligent analytics including Intrusion Detection, Trip Wire, etc. ensure real-time security. Moreover, H.265 compression and Automatic Motion based Frame Rate Reduction save bandwidth and storage up to 50%.

#### **USP**



**SONY STARVIS SENSOR** 



**SMART STREAMING** 



H.265



**ADAPTIVE STREAMING** 



IVA



TRUE WDR



HIGHER FIELD **OF VIEW** 



NAS

#### **CERTIFICATION**













Customer Care: 1800-258-7747 E-mail: Inquiry@MatrixComSec.com www.MatrixVideoSurveillance.com





TECHNICAL SPECIFICATIONS		
IMAGE SENSOR		
Resolution	5 MP (2592 x 1944)	
	1/2.8" SONY - CMOS 5MP Active Pixel	
	Progressive Scan, Back Illuminated Image sensor	
Sensor Type and Size	(EXMOR Technology - STARVIS Series)	
LENS		
	Colour - 0.01 Lux @F1.2 (AGC ON)	
Minimum Illumination	Monochrome - 0 Lux	
Focal Length	6mm	
Focus Range	0.3m to infinity	
	HFOV - 50°	
	VFOV - 37°	
Field of View (FOV)	DFOV - 62°	
Lens Mount	M12	
Focus	Fixed focus	
Aperture (F#)	F 1.6	
Iris Type	Fixed	
IR Range	50m	
IR Led Wavelength	850nm	
IR Switching	Auto/ Manual	
AUDIO INTERFACE		
Audio IN	1	
Audio OUT	1	
Two-way Audio	Supported	
Audio Compression	G.726 and G.711	
Alarm In	Yes	
Alarm Out	Yes	
HARDWARE SPECIFICATIONS		
SD Card	Up to 512GB	
Camera Adjustment Angle	Pan: 0° to 360°	
	Tilt: 0° to 75°	
	Zoom: 0° to 360°	
IMAGE AND VIDEO		
No of Stream Profiles	3	
	Profile 1: 2592X1944 @30fps (H.264/H.265)	
Start of Brackler	Profile 2: VGA @30fps (H.265/H.264)	
Stream Profiles	Profile 3: 2048x1536@8fps (MJPEG)	





	2592 X 1944, 2592 X 1520, 2048 X 1536, 1920 X 1080, 720p, D1, 2CIF,		
Available Resolutions	VGA, CIF, QCIF		
Max Resolution	2592 x 1944		
Bitrate	128kbps-16Mbps		
Bitrate Type	CBR, VBR		
Video Compression	H.265, H.264, MJPEG		
Frame Rate	1-30fps		
Shutter Speed	1/25-1/59000		
Adaptive Streaming	Yes		
ONVIF Profiles	S and G		
Edge Recording	Yes		
Alarm Recording	Pre and Post		
Motion Recording	Yes		
Video Parameters	Snapshot, Region of Interest (ROI), BLC, Day/Night Settings		
Privacy Masks	3		
WDR	True WDR (120dB)		
SNR	73db		
Image Enhancement	Saturation/Contrast/Sharpness/Brightness/Auto Exposure		
DNR	2D &3D		
	Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, IP Conflict, Network		
Video Analytics	Disconnect, Audio Exception, Storage full, Time triggered		
	EVENTS AND ACTIONS		
Upload Image	SD, NAS, FTP		
Upload Clip	SD, NAS, FTP		
Notifications	E-mail, SMS, TCP		
PROTOCOLS SUPPORTED			
	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTCP, RTSP, PPPOE, SMTP,		
Supported protocols	NTP, HTTPS, TLS/SSL, FTP, ICMP, IGMP v2 & v3		
Web Viewer	Supported in IE 8.0-11.0, Firefox 15.0-47.0, Chrome 20.0-54.0		
	IE: Matrix ActiveX		
SI :	Chrome: VLC plugin (2.0.4) and Quicktime(7.7.5)		
Plugins	Mozilla: VLC plugin (2.0.4) and Quicktime(7.7.5)		
OPERATING PARAMETERS			
Power Supply	12V (DC); 802.3af (PoE)		
Power Consumption	<7W		
Operating Humidity	Less than 90% RH (non-condensing)		
Operating Temperature	-20°C to 50°C		
Storage Temperature	-20°C to 50°C		






PHYSICAL PARAMETERS	
Communication interface	10Base-T/100BaseTX Ethernet (RJ-45)
Weight	1410gm
Colour	Pantone 7527C
Dimensions	Ф158 x 134 mm
Storage	NAS, SD Card
Certifications	CE, FCC, ROHS, BIS, IP66, IK10, UL

### 5MP IR Dome Camera with 6mm Lens



### **DIMENSIONS** (in mm)



#### **ABOUT MATRIX**

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology driven and customer focused organization, is committed to keep pace with the revolutions in security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, GSM Gateways, IP Video Surveillance, Access Control and Time-Attendance. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Europe, North America, South America, Africa and Asia through an extensive network of more than 1000 system integrators, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.

\* Specifications are subject to change without prior notice.

Note: Certifications of SATATYA CIDR50FL60CWP shall be available from March'20.